

## LOBA® ParkettOil



### Product description

Classic maintenance oil for oiled parquet and hardwood floors.

### Range of Use

For oiled parquet and hardwood floors. For the maintenance of hand-oiled parquet and hardwood floors, as well as for wood floor elements that have been factory pre-treated with "oxy oils", if the use of maintenance oils is approved by the manufacturer.

Not suitable for use on non-absorbent UV-oiled products.

### Features

- Easy application no polishing necessary
- Maintains anti-slip properties of oiled floors
- Cleaning and maintaining at once possible with the spraycleaner-method

### Technical Data

<b>Article No.</b>	10461	<b>Application Rate</b>	1 litre is sufficient for 100 m <sup>2</sup>
<b>Package Size</b>	5 l, 1 l	<b>Application Tool</b>	Cloth, Wischwiesel, spray can
<b>Packing</b>	Box: 4 x 5 l Pallet: 120 x 5 l Box: 6 x 1 l Pallet: 480 x 1 l	<b>Drying Time</b>	Can be walked on after 4 to 6 hours. Allow to dry overnight before resuming normal usage.
<b>Storage and Transportation</b>	+5°C to + 25°C (41°F to 77°F), storable for 36 months, no hazardous material according to ADR	<b>Thinner</b>	Do not dilute. Product is ready to use.
<b>GISCODE</b>	Ö 60	<b>Contents</b>	Natural oils, aliphatic hydrocarbons, lead-free siccatives

### Application

For newly installed multi-layer flooring elements, as well as freshly oiled floors, clean the floor thoroughly to remove all dust and grit (sweeping, vacuuming) and apply an even coat of ParkettOil using a lint-free cloth or a Wischwiesel, wiping off any excess oil; do not allow the oil to pool or puddle. For floors with stubborn dirt, damp mop with a solution of ParkettSoap, allow floor to dry completely, apply ParkettOil.

For used floors with wear marks, clean thoroughly with LOBA® Cleaner or LOBA® ParkettSoap, if necessary preparing the surface using a floor machine fitted with mildly abrasive pads (beige/green). Allow floor to dry completely. Apply ParkettOil. Floors with more extensive damage may require treatment with impregnation oil. For more information about such treatment, see the LOBA floor-care instructions for oiled hardwood floors.

For larger areas the product can be applied using the SprayCleaner method. Spray ParkettOil onto the floor, and even out the entire area using a floor machine fitted with a white pad.

On non-absorbent surfaces, e.g. newly installed or hardly used parquet and hardwood flooring that were factory finished with UV oil, poor wetting may result. A suitable maintenance product for such flooring is LOBA® NatureWax.

### Caution:

In order to prevent spontaneous combustion, store oil-soaked cloths, pads and other work materials in sealed containers, moisten oil/wax combined with sanding dust, cloths and similar materials with water or store in a bucket with a sealable lid and/or dispose of them in a fireproof container.

**The general information on the use of LOBACARE® products and our current care instructions are part of this information and must be noticed.**