

LOBACARE[®] V6 Finish



Product description

Ready to use long-term polyurethane dispersion. Protects finished floors through a care layer from minor scratches and wear marks. Prevents premature wear and increases the lifetime active. Enhances old dulled floors optically and brings new shine on floors.

Range of Use

Primary care and refreshing of finished hardwood floors, finished cork floors, linoleum and PVC floorings.

Features

- Very durable long-term care product
- Available in glossy and matt
- Good resistance against black-heel marks
- Universally applicable on different floorings

Technical Data

Article No.	10189	Application Rate	approx. 4 l for 100 m ² per application
Gloss level	glossy, matt	Application Tool	LOBATOOL Wischwiesel
Package Size	5 l, 1 l	Drying Time	
Packing	Box: 4 x 5 l Pallet: 128 x 5 l Box: 12 x 1 l Pallet: 480 x 1 l	Can be carefully walked on	after 1-2h
Storage and Transportation	+5°C to + 25°C (41°F to 77°F), storable for 24 months, no hazardous material according to ADR	Fully stressable	after 12h
GISCODE	GE 10	Thinner	Do not dilute. Product is ready to use.
		Contents	(acc. to EU-recommendations): less than 5% anionic surfactants, preservatives. Further ingredients: polymer dispersions, water-soluble solvents
		pH-value	8,7 (glossy) 8,5 (matt)

Preparation:

Floor must be free from dust and soilings. Remove loose dirt and dust in advance with a vacuum cleaner, brush or mop. Afterwards damp mop floor by using LOBA[®] CleanFix or LOBA[®] Cleaner. Residues of old careproducts must be entirely removed with LOBA[®] CareRemove. Therefore please also regard technical informations of the respective products.

Information on Use:

Shake material well. Apply V6 Finish equally on clean, dry floor with a LOBATOOL Wischwiesel (approx. 40 ml/m²). On larger areas a wide-headed wiper mop or another suitable applicator can be used alternatively. Put some of the material on the floor and apply in equally thick coats. Do not put any pressure on the applicator, leave the applicator on the floor during the application, do not lift. Start on one side of the room and work from wall to wall to the other side of the room in direction to the door. Do not process the floor during the drying phase, this could lead to streakings. The floor can be carefully walked on after 1-2h.

Basic Cleaning:

V6 Finish cannot be safely removed by a basic cleaning on cork and wood floors. On some newly installed engineered parquet floorings delaminations might occur. A basic cleaning in advance leads to a sufficient adhesion in most cases.

The general information on the use of LOBACARE[®] products and our current care instructions are part of this information and must be noticed.